







MANUAL VALVES

1. BALL VALVES

	Cod.	Passage (mm) (FULL)		Cod.	Passage (mm) (FULL)
	BK-1/4"	7		BK3L-1/4"	7
	BK-3/8"	10		BK3L-3/8"	10
	BK-1/2"	15		BK3L-1/2"	15
	BK-3/4"	20		BK3L-3/4"	20
	BK-1"	25		BK3L-1"	25
	BK-5/4"	32			
	BK-6/4"	40			
	BK-2"	50			
BK3T Available On Request					
<p>Suitable for industrial, pneumatic and hydraulic installations. Temperature -15° +220° C (AIR), 0° +150° C (WATER WITHOUT STEAM) Pressure -1 +25 bar</p>					

2. GHILUX VALVES

	Cod.	Passage (mm) (FULL)	Dimensions (mm) (LxH)	Temp. -20° +80° C Press. -1 +20 bar
	6310-1/8"	5,5	36 x 31	
	6310-1/4"	5,5	43 x 31	
	6310-3/8"	8	46 x 33	
	6310-1/2"	10	57 x 41	
	Cod.	Passage (mm) (FULL)	Dimensions (mm) (LxH)	Temp. -20° +80° C Press. -1 +20 bar
	6700-1/8"	5	35 x 49	
	6700-1/4"	5	37 x 51	
	6700-3/8"	7	42 x 55	
	Cod.	Passage (mm) (FULL)	Dimensions (mm) (LxH)	Temp. -15° +90° C Press. -1 +10 bar
	6065-1/8"	6	39 x 38	
	6065-1/4"	8	40 x 38	
	6065-3/8"	8	42 x 38	
	6065-1/2"	10	48 x 42	

Technical modifications keep in reserve !

(2019/12)


3. NEEDLE VALVES



Cod.	Passage (mm)	Dimensions (mm) (LxH)	Press. 0 +17 bar
165-1/4"	4	43 x 55	

4. SLIDE VALVES | WITH EXHAUST

ONLY AIR



Cod.	Passage (mm) (FULL)	Dimensions (mm) (L x H)	Temp. -20° +80° C Press. -0.99 +10 bar
6060-1/8"	4	48 x 25	
6060-1/4"	7	58 x 30	
6060-3/8"	10	68 x 35	
6060-1/2"	14	80 x 40	

Technical modifications keep in reserve !

(2021/03)