




ACCESSORIES FOR AIR TREATMENT

1. GAUGES

 (Standard)  (Panel mounting)	Type	Cod.	Con.	Build	Ø (mm)	Range (bar)	Accuracy Class	
	Standard	MANOVAC	1/8"	☐ ▶ A	40	-1 / 0	2.5	
	Standard	MANO-0-4-1/8"	1/8"	☐ ▶ A	40	0 / 4	2.5	
	Standard	MANO-0-10-1/8"	1/8"	☐ ▶ A	40	0 / 10	2.5	
	Standard	MANO-0-10-1/4"	1/4"	☐ ▶ A	50	0 / 10	2.5	
	Panel mounting	MAPA-0-10B-50	1/4"	☐ ▶ A	50	0 / 10	2.5	
	Non-Standard	On request		1/8"	☐ ▶ A	40	-1 / 0	1
					○	50	0 / 1.6	1.6
						63	0 / 2.5	2.5
						100	0 / 4	
						0 / 6		
						0 / 10		
						0 / 16		
						0 / 25		
		0 / 100						
		0 / 400						
		0 / 600						
<u>Options</u> : Case in steel or stainless steel, with slip ring, glycerine filled, with PSI-scale, with calibration-certificate...								

2. LUBRICATION OIL

	Cod.	Volume	Viscosity
	NEVOIL	5 litre	ISO 15

Typicals; Density at 15°C 0,888kg/l; Viscosity 40°C 15,60mm²/s; Viscosity 100°C 3,83mm²/s; Viscosity Index 143; Flash Point COC 152°C; Pour Point -60°C; Acid number 0,40mgKOH/g; Sulphate Ash 0,06%