


SILENCERS

General Specifications:

Maximum Working Pressure : 12 bar
 Working Temperature : -10 until +80 ° C



Cod.	M
7-SFE-M5	M5
1-SFE-1/8"	1/8"
2-SFE-1/4"	1/4"
3-SFE-3/8"	3/8"
4-SFE-1/2"	1/2"





Cod.	M
1-SVL-1/8"	1/8"
2-SVL-1/4"	1/4"
3-SVL-3/8"	3/8"
4-SVL-1/2"	1/2"

(with fine regulator)




Cod.	M
1-SPLF-1/8"	1/8"
2-SPLF-1/4"	1/4"

(max. 6 bar)




Cod.	M
7-SE-M5	M5
1-SE-1/8"	1/8"
2-SE-1/4"	1/4"
3-SE-3/8"	3/8"
4-SE-1/2"	1/2"
5-SE-3/4"	3/4"
6-SE-1"	1"



Cod.	M
1-SVE-1/8"	1/8"
2-SVE-1/4"	1/4"
3-SVE-3/8"	3/8"
4-SVE-1/2"	1/2"

(with regulator)



Cod.	D
AS7100-06	6mm
AS7100-08	8mm
AS7100-10	10mm
AS7100-12	12mm

(max 10 bar)

Technical modifications keep in reserve !

(2019/12)